



Transformer

by ABB




1M000000

Catalog Number 9T10A1324 **Type** QL


75.0 KVA 60 HZ 3 PH 5.2 % IMP
40 C AMB. 150 C RISE 220 C SYSTEM IS-19C

JUMPER CONNECTION	
TAP	VOLTS
1	219
2	212
3	208
4	201
5	198

PRIMARY (X) 208 VOLTS (LINE-LINE)
SECONDARY (H) 240 VOLTS (LINE-LINE)
120 VOLTS (1 PH MIDTAP H1-H4)



COIL TAP ARRANGEMENT



NET WGT
561 LB
254.5 Kg
89246
UY74A

INSPECTION & FINAL TEST
NOG
N137!
091021



X1	-	-	-	-	-	-
H1	-	-	-	-	-	-
X2	-	-	-	-	-	-
H2	-	-	-	-	-	-
X3	-	-	-	-	-	-
H3	-	-	-	-	-	-
X4	-	-	-	-	-	-
H4	-	-	-	-	-	-



ENCLOSURE TYPE 2 (IP20). OR RAINPROOF TYPE 3R (IP22) WHEN PROVIDED SHIELD 9T18Y1074G06

REDUCED CAPACITY TAP RATED AT 5% OF 3 PH KVA

BEFORE HANDLING, INSTALLING AND OPERATING, SEE INSTRUCTION 475A667AAP001

ALUMINUM CONDUCTOR PRIMARY: 10 KV BIL SECONDARY: 10 KV BIL

IN ACCORDANCE WITH NEC SECTION 450-9, ALLOW AT LEAST SIX INCHES CLEARANCE FOR VENTILATION.

CHECK ADDITIONAL NEC AND LOCAL CODE

NEMA CLASS AA DRY TYPE TRANSFORMER

Meets DOE 2016 efficiency

ASSEMBLED IN MEXICO

H4 H3 X3 H2 X2 H1 X1

Note: MID-TAP

Outline: 303B111GEUY74A