



SAFETY DATA SHEET

CADOX M-50A VR

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product label name Methyl ethyl ketone peroxide solution in aliphatic ester	
Supplier Akzo Nobel Polymer Chemicals LLC 525 West Van Buren Street Chicago, IL 60607-3823 www.akzonobel-polymerchemicals.com	
Emergency telephone + 1-914-693-6946 Dobbs Ferry, NY USA	transportation emergency CHEMTREC - USA: 1-800-424-9300 CANUTEC - CANADA: 1-613-996-6666
Intended use Curing agent	
Date of last issue / Revision # 2007/06/01 / 1.02	
Chemical family peroxides	

2. HAZARDS IDENTIFICATION

Emergency overview DANGER! ORGANIC PEROXIDE HEAT OR CONTAMINATION MAY CAUSE HAZARDOUS DECOMPOSITION COMBUSTIBLE LIQUID AND VAPOR CAUSES EYE AND SKIN BURNS MAY BE HARMFUL IF SWALLOWED May cause fire.	
Appearance red liquid with faint odor.	
Health effects Skin and eye contact and inhalation of vapor are the principal routes of exposure to this product. Skin; Causes burns. Eye; Causes burns. Causes injury to the cornea and eyelids. Risk of serious damage to eyes. Harmful if swallowed.	
Carcinogenicity	
Description	Applicable
IARC	no
NTP	no
OSHA	no
ACGIH	no

3. COMPOSITION/INFORMATION ON INGREDIENTS

Information on hazardous ingredients			
Chemical description Methyl ethyl ketone peroxide solution in aliphatic ester			
Composition / information on ingredients			
Number	% w/w	CAS-number	Chemical name
1	30 - 35	001338-23-4	Methyl ethyl ketone peroxide

SAFETY DATA SHEET

CADOX M-50A VR

2	60 - 70	006846-50-0	2,2,4-Trimethyl-1,3-pentanediol diisobutanoate
3	0.0001 - 3	007722-84-1	Hydrogen peroxide
4	0.0001 - 2	000078-93-3	Methyl ethyl ketone
5	0.0001 - 2	007732-18-5	Water

4. FIRST AID MEASURES

Symptoms and effects

Harmful if swallowed. Causes burns. Causes injury to the cornea and eyelids. Risk of serious damage to eyes.

First aid

General

Call a physician immediately.

Inhalation

Remove to fresh air. If not breathing, give artificial respiration. Oxygen may additionally be given, by trained personnel, if it is available. Get medical attention immediately.

Skin

Immediately start continuous flushing of skin with water for at least 15 minutes, while removing contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean or destroy contaminated shoes.

Eye

Immediately start continuous flushing of eyes with water for at least 15 minutes. If easy to do, contact lenses should be removed during the flushing, by trained personnel. Hold the eyelids apart during the flushing to ensure rinsing the entire surface of the eye and lids with water. Get medical attention immediately.

Ingestion

DO NOT induce vomiting. Get medical attention immediately by calling a physician or a poison control center. If victim is conscious and alert, give a cupful of water. Never give anything by mouth to an unconscious or convulsing person. If vomiting occurs, the patient should lie on their left side while vomiting to reduce the risk of aspiration.

Advice to physician

Persons with pre-existing skin, eye, or respiratory disease may be at increased risk from the irritant or allergic properties of this material.

This material is severely corrosive to the eyes and may cause delayed keratitis. The normally prescribed 15 minute eye irrigation after exposure may be difficult because of the severe pain. The prior installation of a topical ocular anesthetic is essential to facilitate a comprehensive ocular lavage. If swallowed, do not induce vomiting. Give patient plenty of water to drink. Ingestion of this corrosive material may result in severe ulceration, inflammation, and possible perforation of the upper alimentary tract, with hemorrhage and fluid loss. Aspiration of this material during induced emesis can result in severe lung injury. Contact a Poison Control Center for additional treatment information. Treat any additional effects symptomatically.

5. FIRE-FIGHTING MEASURES

Extinguishing media

waterspray, alcohol resistant foam, sand, dry chemical powder, CO2.

Unsuitable extinguishing media

halones.

Hazardous decomposition/ combustion products

Carbon dioxide, Carbon monoxide, Water, Acetic acid, Formic acid, Propanoic acid, Methyl ethyl ketone

Protective equipment

Firefighters must wear fire resistant protective equipment. Wear approved respirator and protective gloves.



SAFETY DATA SHEET

CADOX M-50A VR

Other information

Evacuate all non-essential personnel. Extinguish a small fire with powder or carbon dioxide then apply water to prevent re-ignition. Cool closed containers with water. Water used to extinguish a fire should not be allowed to enter the drainage system or water courses. After a fire, ventilate thoroughly the area and soak with water, clean the walls and metallic surfaces.

Fire and explosion hazard

CAUTION: reignition may occur. Decomposition under effect of heating (See also Section Hazardous decomposition products). If involved in a fire, it will support combustion. Vapours may form explosive mixtures with air. In case of fire and/or explosion do not breathe fumes.

NFPA ratings

Hazard classes	Rating
Health	3
Flammability	2
Reactivity	2
Other information	-OX

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

Do not breathe fumes/vapour. Avoid contact with skin and eyes. For personal protection see Section 8.

Environmental precautions

Do not allow to enter drains or water courses.

Methods for cleaning up

Stop leakage if possible. Eliminate all sources of ignition, and do not generate flames or sparks. Collect as much as possible in a clean container for (preferable) reuse or disposal. Cover the remainder with inert absorbent (e.g. vermiculite) for disposal. Keep contents moist. The waste should NOT be confined. Flush surroundings with large amounts of water.

Other information

CAUTION: reignition may occur. Vapours are heavier than air and may spread along floors. Vapours may travel to a source of ignition and flash back. Evacuate personnel to safe area.

7. HANDLING AND STORAGE

Handling

Never weigh out in the storage room. When using do not eat, drink or smoke. Do not pipet by mouth. Do not breathe fumes/vapour. Handle in well ventilated areas. Eliminate all sources of ignition, and do not generate flames or sparks. Keep away from reducing agents (e.g. amines), acids, alkalies and heavy metal compounds (e.g. accelerators, driers, metal soaps). Keep product and emptied container away from heat and sources of ignition. Confinement must be avoided. Avoid contact with skin and eyes. Avoid Incompatible materials (See Section 10).

Fire and explosion prevention

Use explosion protected equipment. Keep away from sources of ignition - No smoking. Use non-sparking tools in area's where explosive vapor air mixtures may occur. Do not cut or weld on or near this container even when empty.

Storage requirements

Store in accordance with local/national regulations. Keep away from food, drink and animal feedingstuffs. Store in a dry well ventilated place away from sources of heat and direct sunlight. Store separate from other chemicals. Keep only in the original container. Keep container upright to prevent leakage.

Storage

For maximum quality store below: 30 °C.



SAFETY DATA SHEET

CADOX M-50A VR

Other information

It is recommended to use electrical equipment of temperature group T3. However, autoignition can never be excluded. Wash hands thoroughly after handling or contact. Keep working clothing separately and do not take them home.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering controls

Ensure good ventilation and local exhaustion of the working area. Explosion proof ventilation recommended.

Personal protection

Respiratory

In case of insufficient ventilation wear suitable respiratory equipment (respirator with Filter A).

Hand

Wear suitable protective gloves of neoprene or synthetic rubber.

Eye

Wear eye/face protection.

Skin and body

Wear suitable protective clothing.

Other information

Emergency-shower and facilities for rinsing eyes must be accessible. Launder clothes before reuse.

Methyl ethyl ketone peroxide

OSHA PEL/CEILING	5 mg/m ³
ACGIH TLV/CEILING	0.2 ppm
NIOSH REL/CEILING	1.5 mg/m ³

Hydrogen peroxide

OSHA TLV/TWA	1.4 mg/m ³
ACGIH TLV/TWA	1 ppm
NIOSH REL/TWA	1.4 mg/m ³
NIOSH IDLH	75 ppm

Methyl ethyl ketone

OSHA TLV/TWA	590 mg/m ³
OSHA PEL/STEL	885 mg/m ³
ACGIH TLV/TWA	200 ppm
ACGIH TLV/STEL	300 ppm
NIOSH REL/TWA	590 mg/m ³
NIOSH REL/STEL	885 mg/m ³
NIOSH IDLH	3000 ppm

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

liquid

Color

red

Odor

faint

Boiling point/range

not applicable (Decomposes)

CADOX M-50A VR

Melting point/range not determined
Flash point Above the SADT value
Flammability Decomposition products may be flammable.
Explosive properties no
Oxidizing properties not applicable
Vapour pressure not determined
Density 1000 kg/m ³ (20°C / 68°F) Specific gravity = 1 (20°C / 68°F)
Bulk density not applicable
Solubility in water Partly miscible with water (20°C / 68°F)
Solubility in other solvents not determined
pH value not determined
Partition coefficient n-octanol/water not determined
Relative vapour density (air=1) not determined
Viscosity not determined
Active oxygen content 8.8 - 9.0 %
Peroxide content 30-35 %
Autoignition temperature Test method not applicable (See Section 7)
SADT 60 °C. See also Section 10.
Explosion limits not determined
Volatile % not determined

10. STABILITY AND REACTIVITY

Stability
SADT - (Self accelerating decomposition temperature) is the lowest temperature at which self accelerating decomposition may occur with a substance in the packaging as used in transport. A dangerous self-accelerating decomposition reaction and, under certain circumstances, explosion or fire can be caused by thermal decomposition at and above the following temperature: 60 °C. Contact with incompatible substances can cause decomposition at or below the SADT 60 °C.

CADOX M-50A VR

Conditions to avoid	
	To maintain quality store in original closed container below: 30 °C.
	Confinement must be avoided.
Incompatibles	
Avoid contact with rust, iron and Copper. Contact with incompatible materials such as acids, alkalies, heavy metals and reducing agents will result in hazardous decomposition. Do not mix with peroxide accelerators. Use only Stainless steel 316, PVC, polyethylene or glass-lined equipment.	
Polymerization	
Polymerization does not occur.	
Decomposition	
Acetic acid, Formic acid, Propanoic acid, Methyl ethyl ketone	
Other information	
Emergency procedures will vary depending on conditions. The customer must have an emergency response plan in place. Contact Akzo Nobel for assistance with developing an emergency response plan.	

11. TOXICOLOGICAL INFORMATION

No experimental toxicological data on the preparation as such available. The following data are applicable to the ingredient(s) listed below.	
Methyl ethyl ketone peroxide, 40 % in Dimethyl phthalate	
	Acute toxicity
	Oral LD50 rat:1017 mg/kg
	Dermal LD50 rat:4000 mg/kg
	Inhalation LC50 rat:17 mg/l ; 4 hours exposure time
	Irritation
	Skin Corrosive
	Eye Corrosive
	Sensitization Not sensitizing
	Genotoxicity Ames test: Not mutagenic
Methyl ethyl ketone	
	Acute toxicity
	Oral LD50 rat: 2737 mg/kg
	Dermal LD50 rabbit 6480 mg/kg
	Inhalation LC50 rat 23.5000 mg/m ³
	Irritation
	Skin Moderately irritating

SAFETY DATA SHEET

CADOX M-50A VR

Eye Moderately irritating

12. ECOLOGICAL INFORMATION

No experimental ecological data are available on the preparation as such. The following data are applicable to the ingredient(s) listed below.	
Methyl ethyl ketone peroxide, 40 % in Dimethyl phthalate	
Ecotoxicity	
fish	Acute toxicity, 96h-LC50 = 44.2 mg/l. (Poecilia reticulata.)
bacteria	Activated sludge respiration inhibition test EC50 = 48.0 mg/l.
Fate	
Degradation Biotic	Readily biodegradable (Closed bottle test).
Methyl ethyl ketone	
Ecotoxicity	
fish	Lepomis macrochirus: 96h-LC50: 3.22 g/l
Fate	
Degradation Biotic	Readily biodegradable.
Other information	Naturally occurring substance

13. DISPOSAL CONSIDERATIONS

Product	Due to the high risk of contamination recycling/recovery is not recommended. Waste disposal in accordance with regulations (most probably controlled incineration).
Contaminated packaging	According to local regulations. Emptied container might retain product residues. Follow all warnings even after the container is emptied.
Other information	For further advice contact manufacturer.

14. TRANSPORT INFORMATION

<i>Land transport</i>	
Class	5.2
Packing group	II
TREM-Card or ERG number	NA ERG No.: 145
UN number	UN3105
Proper Shipping Name	Organic peroxide type D, liquid; (Methyl ethyl ketone peroxide <=45%.)



SAFETY DATA SHEET

CADOX M-50A VR

Other information This product contains methyl ethyl ketone peroxide (RQ=10 lbs.) which is an environmentally hazardous substance per 49 CFR 172.101, Appendix A.
Required labels Label(s); 5.2

<i>Sea transport (IMDG-code/ IMO)</i>
Class 5.2
UN number 3105
EMS F-J, S-R
Marine pollutant no
Proper Shipping Name Organic peroxide type D, liquid; (Methyl ethyl ketone peroxide (s))
Other information Label(s); 5.2

<i>Air transport (ICAO-TI/ IATA-DGR)</i>
UN number 3105
Class 5.2
Proper Shipping Name Organic peroxide type D, liquid; (Methyl ethyl ketone peroxide (s))
Other information Label(s); 5.2

15. REGULATORY INFORMATION

Product and or components listed below are subject of the following	
Methyl ethyl ketone peroxide	
CERCLA Hazardous Substance	yes (RQ = 10 LB)
Massachusetts Substance List	yes
New Jersey R-T-K Hazard. Sub.	yes
Penn. Hazardous Substance list	yes
Toxic Subst. Cont. Act -listed	yes
Non-Domestic Subst.List-Canada	no
Domestic Substance List-Canada	yes
California Hazardous Substances	yes
Connecticut Hazardous Material Survey	yes
Minnesota Hazardous Substance	yes
New York Hazardous Substances	yes



SAFETY DATA SHEET


CADOX M-50A VR

Rhode Island Hazardous Substances	yes
2,2,4-Trimethyl-1,3-pentanediol diisobutanoate	
Toxic Subst. Cont. Act -listed	yes
Non-Domestic Subst.List-Canada	no
Domestic Substance List-Canada	yes
Hydrogen peroxide	
IARC Carcinogens-Grps. 1,2A,2B	
Massachusetts Substance List	yes
New Jersey R-T-K Hazard. Sub.	yes
Penn. Hazardous Substance list	yes
SARA Title III, Section 302	yes
Toxic Subst. Cont. Act -listed	yes
Non-Domestic Subst.List-Canada	no
Domestic Substance List-Canada	yes
California Hazardous Substances	yes
Connecticut Hazardous Material Survey	yes
Illinois Toxic Substances Disclosure to Es	yes
Louisiana RTK Reporting	yes
Minnesota Hazardous Substance	yes
New York Hazardous Substances	yes
Rhode Island Hazardous Substances	yes
Methyl ethyl ketone	
CERCLA Hazardous Substance	yes (RQ = 5000 LB)
Massachusetts Substance List	yes
New Jersey R-T-K Hazard. Sub.	yes
Penn. Hazardous Substance list	yes
Toxic Subst. Cont. Act -listed	yes
Non-Domestic Subst.List-Canada	no
Domestic Substance List-Canada	yes
California Hazardous Substances	yes
Connecticut Hazardous Material Survey	yes
Illinois Toxic Substances Disclosure to Es	yes
Minnesota Hazardous Substance	yes
New York Hazardous Substances	yes
Rhode Island Hazardous Substances	yes
Water	
Toxic Subst. Cont. Act -listed	yes
Non-Domestic Subst.List-Canada	no
Domestic Substance List-Canada	yes

Hazard classes	
Description	Applicable
EPA Immediate health	yes
EPA Delayed health	no

SAFETY DATA SHEET

CADOX M-50A VR

EPA Fire	yes
EPA Pressure	no
EPA Reactive	yes
EHS Material	yes
Hazard Rating Source	HMIS
HMIS Health	3
HMIS Flammability	2
HMIS Reactivity	2
WHMIS Hazard classes	B-3,C,D-2B,E,F
	
NFPA Flammability	3
NFPA Health	2
NFPA Reactivity	2
Other regulatory information This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all of the information required by the Controlled Products Regulations	

16. OTHER INFORMATION

History
Other information CADOX: This is a registered trademark of Akzo Nobel Chemicals BV or any of its affiliated companies in one or more territories in the world.
Date of printing/ pdf file generated 2007/10/05
Revision 1.02
Composed by N. Shoshenskiy, Regulatory Affairs - North America.J.W. Wessels - Regulatory Affairs - Europe.
Changes were made in section 1, 2, 3
<small>The information in this material safety data sheet should be provided to all who will use, handle, store, transport or otherwise be exposed to this product. All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable as of the date of publication. However, no warranty is made as to the accuracy of and/or sufficiency of such information and/or suggestions as to the merchantability or fitness of the product for any particular purpose, or that any suggested use will not infringe any patent. Nothing in here shall be construed as granting or extending any license under any patent. Buyer must determine for himself, by preliminary tests or otherwise, the suitability of this product for his purposes, including mixing with other products. The information contained herein supersedes all previously issued bulletins on the subject matter covered. If the date on this document is more than three years old, call to make certain that this sheet is current.</small>