

PowerMark Gold® Load Centers

100-125 Amp, 12/22/24 Circuit



More breaker capacity

- 14 1" breakers
- 24 total breaker spaces

Easier installation

- New knockout layout includes 6 tangential knockouts, eliminates 3/8" knockout
- Slotted mounting holes for adjustable depth
- Centered key holes for ease of mounting
- Ground bar included

Improved safety features


- Insulation tube protects ground bar from main lug wires
- Single Phase, Three Wire, 120/240 VAC, 22 kAIC rated
- UL Listed (Panelboards No. 67)
 - Service barriers included for factory installed main circuit breaker
- 60°C/75°C conductor rating
- Suitable for use as Service Entrance Equipment when installed in accordance with the National Electric Code


Technical Data


Indoor Type 1 Enclosure, Combination Flush/Surface Front

	Maximum Spaces						Enclosure					Main	Equipment
Main Ampere	1 Pole 2 Pole		1 Pole 2 Pole		Total Main Style 1 Pole (Factory				ns (in)	Catalog	Wire Size (AWG/kcmil)	Ground Kit ¹ (Order	
Rating	1" THQL		1/2"	THQP	Spaces	Installed)		W	Н	D	Number		Separately)
125	14	6	20	8	24	Main Lug	18	14	16	3/38	TLM1212CCU	6-2/0	TGL2 & TGL20
	12	5	20	8	22	Main Breaker					TM1212CCU		
100	12	5	20	8	22	Main Breaker					TM1210CCU		

¹ Load center includes a factory installed ground bar and add-a -lug (see wiring diagram below). A separate TGL2 can be added if additional ground bar is required.







Knockouts

Symbol	В	D	K	AA
	1/2	1/2		
_		3/4	3/4	3/4
Conduit			1	1
Size (inches)			11/4	11/4
(11/2	11/2
_				2




ABB Inc 305 Gregson Drive Cary, NC 27511 www. electrification.us.abb.com

Information provided is subject to change without notice. Please verify all details with ABB. All values are design or typical values when measured under laboratory conditions, and ABB makes no warranty or guarantee, express or implied that such performance will be obtained under end-use conditions.

 $[\]ensuremath{\texttt{©}}$ Copyright 2019 ABB. All rights reserved.