



| DIMENSIONS |      |      |      |
|------------|------|------|------|
| Size       | A    | B    | C    |
| 3/4"       | 3.87 | 2.58 | 1.85 |



**MATERIAL SPECIFICATION**

| PART                          | MATERIAL                             | SPECIFICATION           |
|-------------------------------|--------------------------------------|-------------------------|
| 1 Body                        | Lead-free forged brass               | CW510L UNS Alloy C28500 |
| 2 Stem                        | Lead-free chrome-plated forged brass | CW510L UNS Alloy C28500 |
| 3 Anti-friction thrust washer | PTFE                                 | Teflon*                 |
| 4 Stem-O-ring (2)             | EPDM rubber                          | Commercial grade        |
| 5 Downstream seat             | PTFE                                 | Teflon*                 |
| 6 Ball                        | Lead-free chrome-plated forged brass | CW510L UNS Alloy C28500 |
| 7 Anti-friction washer        | PTFE                                 | Teflon*                 |
| 8 Handle                      | Dacromet-coated steel                | Commercial grade        |
| 9 Handle nut with resin lock  | Dacromet coated steel and PVC        | Commercial grade        |
| 10 End adapter                | Lead-free forged brass               | CW510L UNS Alloy C28500 |
| 11 Upstream seat              | NBR (Buna-N)                         | Commercial grade        |

\*Teflon is a registered trademark of DuPont.

Lead-free design is suitable for all no-lead potable water installations, in full compliance of all lead-free plumbing laws.

Forged brass construction eliminates casting-related leaks.

The positive-shutoff ball-and-seat design is a more durable alternative to traditional stop-type valve designs.

Maintenance-free dual O-ring stem seal eliminates the need for packing-nut tightening.

Smooth quarter-turn operation with all handle configurations.

Ideal for all residential and commercial hose bib requirements.

**Working Pressure, non-shock (PSI)**

Cold working pressure (CWP): 200 p.s.i.

Saturated steam (WSP): Not suitable for steam service

- Third-party tested and certified in compliance with U.S. Federal Public Law 111-380 (National lead-free plumbing law).
- Certified to ANSI / NSF Standard 61-G
- End connections comply with:  
ANSI / ASME B1.20.1 (MNPT)  
ANSI / ASME B16.18 (CTS solder)
- Manufactured in an ISO accredited facility



Midwest Electric Products  
Plainville, CT

MIDWEST 3/4 Turn HOSE BIB - LEVER

| CAT NO    | DWG DATE   | REV # |
|-----------|------------|-------|
| UWATER34L | 11/21/2016 | 01    |